



| | B910 |
|-----------------------------------|---|
| Model | B910 |
| Product Type | Mini PTZ |
| Maximum Resolution | 4MP |
| Application Environment | Outdoor |
| Image Sensor | Progressive Scan CMOS |
| Day / Night | Yes |
| Superior Low Light Sensitivity | Yes |
| Minimum Illumination | Color: 0.1 lux, B/W: 0.05 lux at F1.8 |
| Mechanical IR Cut Filter | Yes |
| IR LED | No |
| Lens | Zoom, f4.9-49mm / F1.8-3.0, DC iris, Auto focus |
| Zoom Ratio | 10x optical |
| Panning and Tilting Range | Pan: -175°-175°, Tilt: 0°-180° (with E-flip) |
| Lens Mount | Board mount |
| Horizontal Viewing Angle | 52.12°-5.9° |
| Compression | H.264 High Profile, MJPEG |
| Maximum Frame Rate vs. Resolution | 15 fps at 2688 x 1520 15 fps at 2560 x 1440 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 640 x 480 15 fps at 320 x 240 |
| Horizontal Resolution (TV lines) | 1500 TVL |
| Multi-Streaming | Dual streams |
| Wide Dynamic Range | Basic WDR (70 dB) |
| Digital Noise Reduction | DNR |
| S/N Ratio | 52 dB |
| Audio | 2-way (Line-in, Line-out) |
| Network Protocol & Service | TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour |
| Pan, Tilt or Zoom protocol | Visca, Pelco-D, Pelco-P |
| Network Connector | RJ-45 |
| Digital Input/Output | 1/1 |
| | MicroSDHC/MicroSDXC memory card slot |

| | |
|--|--|
| Local Storage | microSDHC/microSDXC memory card slot (card not included) |
| Power Source | DC 12V; PoE Class 3 |
| Environmental Casing | Weatherproof (IP67); Vandal proof (IK10) |
| Bundled Accessories | No |
| Mount Type | Surface, Pendant, Wall, Corner, Pole, Flush, Gang Box |
| Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server) | Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection |
| Client PC Operating System | Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP |
| PC Web Browser | IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime |
| ONMF Compliant | Yes |
| Starting Temperature | -40°C ~ 50°C (-40°F ~ 122°F) within 30 minutes |
| Operating Temperature | -40°C ~ 50°C (-40°F ~ 122°F) |
| Approvals | CE, FCC, IP67, NEMA4X, IK10 |
| Warranty | 3 Years* (3 Months in continuous motion) |
| Product Availability | ACTi : 2014.12.04 Distributor : 2015.01.04 |
| MSRP (local, reference only) | Please contact our sales |