

	E66A
Model	E66A
Product Type	Dome
Maximum Resolution	1.3MP
Application Environment	Indoor
Image Sensor	Progressive Scan CMOS
Day/Night	No
Superior Low Light Sensitivity	Yes
Mnimum Illumination	Color: 0.1 lux at F1.4
Mechanical IR Cut Filter	No
IRLED	No
Lens	Vari-focal, f2.8-12mm / F1.4, Fixed iris, Manual focus
Viewing Angle Adjustment	Pan: 0°-350°, Tilt: 17°-163°, Rotate: 0°-350°
Lens Mount	Board mount
Horizontal Viewing Angle	83.0°-31.1°
Compression	H.264 High Profile, MJPEG
Maximum Frame Rate vs. Resolution	30 fps at 1280 x 960 60 fps at 1280 x 720 30 fps at 800 x 600 30 fps at 640 x 480 15 fps at 320 x 240
Horizontal Resolution (TV lines)	950 TVL
Multi-Streaming	Dual streams
Wide Dynamic Range	Basic WDR (88 dB)
Digital Noise Reduction	DNR
S/N Ratio	52 dB
Audio	2-way (Line-in, Line-out)
Network Protocol & Service	TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
Network Connector	RJ-45
Digital Input/Output	1/1
Local Storage	McroSDHC/McroSDXC memory card slot (card not included)
Power Source	PoE Class 2

Environmental Casing	Vandal Resistant (IK09)
Bundled Accessories	No
Mount Type	Surface, Pendant, Wall, Corner, Pole, Flush, Gang Box
Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server)	Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
Client PC Operating System	Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
PC Web Browser	IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime
ONVIF Compliant	Yes
Starting Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Approvals	CE, FCC, IK09
Warranty	3 Years
Product Availability	ACTi : Now Distributor : Now
MSRP (local, reference only)	Log-in required